

[battu00141 laptop battery](#) [folded bicycle bike](#) [新华第一原油直播室](#) [e bike battery price](#) [伊通满族自治县成人教育网_定州市综合新闻导报](#) [power assisted bicycle](#) [泡妞秘籍](#) [北京赛车技巧](#) [ebike battery pack](#) [朋友局官网](#)

The Mavic Crossmax XL Pro WTS has everything you are looking for in terms of being lightweight, rugged, and dependable. Mavic brings forth the best of their technologies for this wheelset. These are designed to hold up when technical trails force you to strain your mind, reaction time, and bike. The lighter 23mm rims (27mm external) has extra support where it could be venerable to sudden changes in handling. Thanks to ISM (Inter Spoke Milling) even more weight is saved by machining in between the spokes without overlooking the overall strength. The rims have reinforced sidewalls to allow your mental movements to become a reality as you navigate the tight turns and unexpected drops that turn up in the wilderness. There are 24 Mavic Bladed Zicral spokes to balance the rigidity with power. The front wheel has crossed spokes to absorb shock as you ride. Meanwhile, the rear wheel uses Mavic's laced Isopulse principle to efficiently transfer your pedaling power into the ground. The ITS 4 freewheel system is compatible with multiple hub set ups. This system only needs 7.5 degrees of engagement to get your power into action faster than ever. These rims are tubeless compatible giving you the option to ride with tubes or without. The Mavic Crossmax Quest Tires are versatile and balanced overall. Whether you are looking for cornering grip, general traction, or rolling efficiency this tire has it all. There are soft side knobs for cornering while the center tread is designed to roll quickly. The hubs are compatible with 9/15/20 or Lefty Supermax (2.0) for the front wheel. The rear wheel comes with adaptors for 9/12x135/142 and is available with the HG10 or Sram XD driver body. Available in Limited Edition Yellow in 27.5x2.4 with Sram XD, 27.5x2.25 with Sram XD, 27.5x2.4 with Sram XD, or 26x2.4 with Shimano HG10. Details:RIMS

Material: Maxtal

Drilling: Fore

Weight reduction: ISM

Tire: UST Tubeless or Tubes

Internal width: 23 mm

ETRTO size 26": 559x23C

ETRTO size 27.5": 584x23C

ETRTO recommended tire sizes: 37 mm to 76 mm (1.5" to 3.0")

SPOKES

Material: Zicral

Shape: straight pull, round

Nipples: Fore integrated aluminum

Count: 24 front and rear

Lacing: front crossed 2, rear Isopulse

HUBS

Front and rear bodies: aluminum

Axle material: aluminum

Adjustable sealed cartridge bearings

Freewheel: ITS-4 alloy

Shimano 11 speeds compatible with optional kit

Sram XD Compatible (XX1-X01) with optional kit

TIRE

Crossmax Quest

UST Tubeless Ready

Casing: 66 TPI

Dimension 26": 2.40

Dimension 27.5": or 2.25 2.40

VERSIONS – REAR

HG or XD driver body

DELIVERED WITH

BX601 rear quick release

1 bottle of Mavic Sealant

UST valve and accessories

Front 15 mm adapters

Rear QR adapters

Rear 12x142mm adapters

Multifunction adjustment wrench

User guide